

Cutterbars			
Front attachments			
VARIO cutterbars		VARIO 1230, VARIO 1080, VARIO 930, VARIO 770	
CERIO cutterbars		CERIO 930, CERIO 770	
Rapeseed equipment		For all VARIO cutterbars, not available for CERIO cutterbars	
Folding cutterbars		C 540, C 450	
SUNSPEED	rows	12, 16	
MAXFLEX		MAXFLEX 1200, MAXFLEX 1050, MAXFLEX 930, MAXFLEX 770	
MAXFLO		MAXFLO 1200, MAXFLO 1050, MAXFLO 900	
VARIO rice cutterbars		Available as HD version with rice harvesting accessory pack	
CERIO rice cutterbars		Available as HD version with rice harvesting accessory pack	
SWATH UP		SWATH UP 450	
Variable speed drive front attachment, electrohydraulic	rpm	284-420	
Front attachment step drive	rpm	332, 420	
Instant cutterbar brake		○	
Standard cutterbars			
Effective cutting widths		CERIO 930 (9.22 m), CERIO 770 (7.70 m)	
Drive		Single-side gear drive	
Folding dividers		●	
Spacing: knife bar – intake auger	mm	480-680, manually adjustable	
Cutting frequency	strokes/min	1218	
Multifinger intake auger		●	
Reverser, hydraulic		●	
Automated cutterbar control			
CONTOUR		●	
AUTO CONTOUR		○	
Reel speed control		●	
Reel height adjustment		●	
Parked position		●	
Replacement knife bar		●	
Crop lifters		●	
VARIO cutterbars			
Effective cutting widths		VARIO 1230 (12.27 m), VARIO 1080 (10.74 m)	VARIO 930 (9.22 m), VARIO 770 (7.70 m)
Drive		Synchronised gear drives on both sides	Single-side gear drive
Folding dividers		●	●
Spacing: knife bar – intake auger	mm	490-1135, 700 mm continuously adjustable travel range	490-1135, 700 mm continuously adjustable travel range
Knife bar		Divided, synchronised drive on both sides	Undivided
Cutting frequency	strokes/min	1218	1218
Reel and auger bearing		Divided reel and intake auger with central bearing	Undivided reel and auger
Intake auger diameter		660	660
Automated cutterbar control			
CONTOUR		○	●
AUTO CONTOUR		●	○
Reel speed control		●	●
Reel height adjustment		●	●
Reel levelling system		●	●
Table positioning		●	●
Parked position		●	●
Replacement knife bar		●	●
Crop lifters		●	●